

# AF4.5

P/N 100016



### SlimLine fixed 4.5 Hz shallow borehole seismometer

The AF4.5 is ASIR's readily deployed shallow posthole and borehole 3-component seismometer for use in microearthquake detection and monitoring. The AF4.5 is designed for up to 200 m depths with tilts of up to 3°. Features the highest current performance level in sensitivity, reliability, and longevity.



#### Features

- > slim 51 mm outer diameter (OD)
- > passive geophone sensors
- > for permanent or temporary installations

#### Sensor Parameters

Coil Resistance	3400 Ohms $\pm$ 10 %
Depth Range	0 - 200 m
Distortion	< 0.3 %
Max Motion p-p	4 mm
Moving Mass	11.3 g
Natural Frequency	4.5 $\pm$ 0.5 Hz
Open Circuit Damping	0.58 $\pm$ 20 %
Operating Temperature	-40 to +70 °C
Sensitivity	82 V/m/s $\pm$ 7.5 %
Sensor Type	3 component - fixed
Tilt Tolerance	3°

#### Sonde Dimensions

Height	420 mm
Outer Diameter	51 mm
Weight	2.6 kg

#### Cable

Delivered standard with 3 twisted shielded pairs, 300 kg Kevlar core, non-armored. Can be supplied with cable to meet customer specified requirements and length.